



PRESENTS
2009 ALL-STARS

THE SPECIALISTS



RAPIDGUN & ERG
PNEUMATIC WRENCHES

RAPID-TORC is an International Corporation, based in Houston, TX and Brussels, Belgium. Leader in the Bolting market, the company designs, manufactures and distributes high quality hydraulic torque wrenches, bolt tensioners and induction heating systems and delivers value-added technical services to customers worldwide.

POWERFUL AND HANDHELD.

RG Series features



- Produces torque over 6,800Nm/5000 ft. lbs
- Extremely quiet, produces noise at only 75db
- Low vibration at only 2.5m/s²
- Tooling accuracy guaranteed within +/-5%

Patented planetary design
Unmatched design for torque delivery

3 square drive sizes available
(3/4", 1" and 1 1/2")
Most common sizes in stock for quick delivery

Durable casing
Will withstand years of service

Ergonomic handle
The handle was designed to allow easier handling of the tool



Easy-to-use Forward/Reverse
Speeds up work pace thanks to placement of the forward/reverse function

Standard reaction arm
The standard reaction arm is included with your purchase...it is highly durable

Soft-start trigger
Avoids operator exhaustion with this 'feather touch' feature

RAPIDGUN carrying case
increases the portability of your machine. It comes standard



| Model | Drive | Torque | | RPM | Weight (kg) |
|---------|--------|-----------|-----------|-----|-------------|
| | | Nm | Ft.lbs | | |
| RG-1100 | 3/4" | 200-1100 | 150-800 | 30 | 4.3 |
| RG-2400 | 1" | 700-2450 | 500-1800 | 10 | 5.6 |
| RG-4000 | 1" | 1400-4050 | 1000-3000 | 14 | 9.2 |
| RG-6800 | 1 1/2" | 2000-6800 | 1500-5000 | 7 | 12.7 |

Available
Reaction
Arms:



Blank



Double Blank

RAPIDGUN IS THE HANDHELD SOLUTION FOR TORQUING NEEDS.

- Produces torque over 5,400Nm/3,982 ft. lbs
- Extremely quiet, produces noise at only 75db
- Low vibration at only 2.5m/s²
- Tooling accuracy guaranteed within +/-3%
- Repeatability accurate at +/-2%
- Lightweight and non-impacting

ERG Series features



Waterproof regulator case
15ft cable + Data Collection Software

| Model | Drive | Torque | | Rpm | Weight (kg) |
|----------|--------|-----------|----------|-----|-------------|
| | | Nm | ft-lbs | | |
| ERG-2700 | 1" | 400-2700 | 295-1991 | 30 | 8.1 |
| ERG-5400 | 1 1/2" | 1085-5400 | 796-3982 | 10 | 14.0 |

Point

Double ended

Fork



SERVICE ON SITE



RAPID-TORC, INC
715 Bradfield
Houston, TX 77060
USA

Phone: (281) 448-5900
Fax: (281) 260-0779

RAPID-TORC, S.A.
Avenue Louise, 306
B-1050 Brussel
Belgium

Tel: +32 2 358 1933
Fax: +32 2 358 5066

www.rapidtorc.com
sos@rapidtorc.com